

## Technical Data Sheet

Product Name: **Mineral Filled Polypropylene Compound**

Grade: **RP71PRLI-40TD-B**

### Description:

**RP71PRLI-40TD-B** is recycled polypropylene filled with talc. It provides good stiffness and dimensional stability. This compound has been specifically designed for automotive plastics parts. Its main application is injection molding process.

### General Information:

<b>Material Status:</b>	<i>Commercially Active</i>
<b>Delivery form:</b>	<i>Pellets</i>
<b>Color:</b>	<i>Black</i>
<b>Processing Method:</b>	<i>Injection Molding</i>
<b>Application:</b>	<i>Automotive parts</i>
<b>Packing:</b>	<i>25 kg</i>

### Characteristics:

	<i>Value</i>	<i>Unit</i>	<i>Test method</i>
Density	1.2	gr/cm <sup>3</sup>	ASTM D 792
MFI (230 °C, 2.16 Kg)	8	gr/10min	ASTM D 1238
Tensile Strength (50 mm/min)	18	MPa	ASTM D 638
Flexural Modulus	2500	MPa	ASTM D 790
Izod Notched Impact Strength	30	J/m	ASTM D 256

### Recommendation:

- *The recommended processing temperature is 160 to 230 °C*
- *Store in dry place away from direct sun exposure*

*Published July, 2021*

**Web-site:** [www.rayanbaspar.com](http://www.rayanbaspar.com)

**E-mail:** [rayanbaspar.ind@gmail.com](mailto:rayanbaspar.ind@gmail.com)

**Tel:** +98 21 4478 7085

**Fax:** +98 21 4478 7085

**Address:** Polymer Technology Incubator (IPPI), Km 15, Tehran-Karaj high way, Tehran, Iran