

Technical Data Sheet

Product Name: **Mineral Filled Polypropylene Compound**

Grade: **RP71PRMI-20TD-B**

Description:

RP71PRMI-20TD-B is recycled polypropylene filled with talc. It provides good impact strength and dimensional stability. This compound has been specifically designed for automotive plastics parts. Its main application is injection molding process.

General Information:

Material Status:	<i>Commercially Active</i>
Delivery form:	<i>Pellets</i>
Color:	<i>Black</i>
Processing Method:	<i>Injection Molding</i>
Application:	<i>Automotive parts</i>
Packing:	<i>25 kg</i>

Characteristics:

	<i>Value</i>	<i>Unit</i>	<i>Test method</i>
Density	1.05	gr/cm ³	ASTM D 792
MFI (230 °C, 2.16 Kg)	8	gr/10min	ASTM D 1238
Tensile Strength (50 mm/min)	20	MPa	ASTM D 638
Flexural Modulus	1700	MPa	ASTM D 790
Izod Notched Impact Strength	7	KJ/m ²	ASTM D 256

Recommendation:

- *The recommended processing temperature is 160 to 230 °C*
- *Store in dry place away from direct sun exposure*

Published July, 2021

Web-site: www.rayanbaspar.com

E-mail: rayanbaspar.ind@gmail.com

Tel: +98 21 4478 7085

Fax: +98 21 4478 7085

Address: Polymer Technology Incubator (IPPI), Km 15, Tehran-Karaj high way, Tehran, Iran