

Technical Data Sheet

Product Name: ***Polyamide Reinforced with Glass Fiber***

Grade: ***RP73PAR-30GF-B***

Description:

RP73PAR-30GF-B is polyamide reinforced with 30 % glass fiber. It combines excellent mechanical properties and toughness and also appropriate thermal resistance. This grade provides high stiffness and dimensional stability, simultaneously. This compound has been designed for injection molding process and its main application is automotive parts, electrical goods and other finished products.

General Information:

Material Status:	<i>Commercially Active</i>
Delivery form:	<i>Pellets</i>
Color:	<i>Black</i>
Processing Method:	<i>Injection Molding</i>
Application:	<i>Automotive Plastics Parts, Electrical Plastics Parts</i>
Packing:	<i>25 kg</i>

Characteristics:

	<i>Value</i>	<i>Unit</i>	<i>Test method</i>
Density	1.3	gr/cm ³	ASTM D 792
Tensile Strength (50 mm/min)	≥120	MPa	ASTM D 638
Elongation	5	%	ASTM D 638
Flexural Modulus	8000	MPa	ASTM D 790
Izod Notched Impact (23 °C)	12	KJ/m ²	ASTM D 256
Izod Un-Notched Impact (23°C)	NB	KJ/m ²	ASTM D 256

Recommendation:

- *It should be degassed properly before using*

Published July, 2021

Web-site: www.rayanbaspar.com

E-mail: rayanbaspar.ind@gmail.com

Tel: +98 21 4478 7085

Fax: +98 21 4478 7085

Address: Polymer Technology Incubator (IPPI), Km 15, Tehran-Karaj high way, Tehran, Iran