Rayan Polymer Industry



Masterbatches, Compounds and Polymer Additives Supplier

Technical Data Sheet

Product Name: Anti-Oxidant Masterbatch

Grade: RP76A01

Description:

RP76AO1 is a high quality anti-oxidant masterbatch containing best kinds of additives in polyethylene resin. This grade provides excellent protection against thermal and chemical degradation of polymer during processing. It also improves product performance in the long term applications. The main application of this grade is pipe and profile extrusion lines, blown films and packaging industry, and also is suitable for using in HDPE, LDPE, EVA and PP.

General Information:

Material Status: Commercially Active

Delivery form: Pellets
Color: Colorless

Processing Method:Pipe extrusion lines, Blown films, Injection molding, etcApplication:Different size pipes, Agriculture films, Packing films

Packing: 25 kg

Characteristics:

	Value	Unit	Test method
Density	0.95	gr/cm ³	ASTM D 792
MFI (190 °C, 2.16 Kg)	5	gr/10min	ASTM D 1238

Recommendation:

- The recommended dosage is 1 to 4 % depending on desired final application of product
- Store in dry place away from direct sun exposure
- The appropriate shelf life is 24 months after producing date
- The recommended dosage for obtaining $OIT \ge 20$ min is 2 to 4 % in virgin and recycled PE

Published July, 2021

 Web-site:
 www.rayanbaspar.com
 Tel: +98 21 4478 7085

 E-mail:
 rayanbaspar.ind@gmail.com
 Fax: +98 21 4478 7085

Address: Polymer Technology Incubator (IPPI), Km 15, Tehran-Karaj high way, Tehran, Iran