

Technical Data Sheet

Product Name: **Impact Modifier and Compatibilizer Masterbatch**

Grade: **RP79AC+**

Description:

RP79AC+ is a maleic anhydride grafted polyolefin elastomer (POE) which is compatibilized using some special additives. RP79AC+ is mainly used as impact modifier of virgin and recycled polyamide and also glass fiber reinforced polyamide compounds, surface modifier in highly filled composites and compatibilizer in polymer alloys. It provides superior compatibility and toughness in reinforced compounds.

General Information:

Material Status:	<i>Commercially Active</i>
Delivery form:	<i>Pellets</i>
Color:	<i>Colorless</i>
Processing Method:	<i>Injection Molding, Compounding</i>
Application:	<i>Impact modifier, Coupling agent, Compatibilizer</i>
Packing:	<i>25 kg</i>

Characteristics:

	<i>Value</i>	<i>Unit</i>	<i>Test method</i>
Density	0.9	gr/cm ³	ASTM D 792
MFI (190°C, 2.16 Kg)	≤ 3.5	gr/10min	ASTM D 1238
Melting Point	≥ 80	°C	DSC analysis
Maleic Content	High	%	Internal method

Recommendation:

- *The recommended dosage for impact modifying of PA is 5 to 15 %*
- *The recommended dosage for glass fiber reinforced compounds is 2 to 5 %*
- *Store in dry place away from direct sun exposure and below 30 °C*

Published Jan, 2024

Web-site: www.rayanbaspar.com

E-mail: rayanbaspar.ind@gmail.com

Tel: +98 21 4478 7085

Fax: +98 21 4478 7085

Address: Polymer Technology Incubator (IPPI), Km 15, Tehran-Karaj high way, Tehran, Iran